



Powering Innovation



PROTECTION + AUTOMATION + CONTROL

ELECTRICAL RESET TRIPPING RELAY

JRV 192 T

JVS ELECTRONICS PVT. LTD.

#121, Manchanayakanahalli,
Bangalore Mysore Highway, Bidadi,
Ramanagara District - 562 109, Karnataka, India
+91 94808 26272, +91 94808 26260
bangalore@jvselectronics.in, www.jvselectronics.in

FEATURES

- ◆ Wide range of voltage & contacts configurations
- ◆ Electromechanical design
- ◆ Electrical reset contacts
- ◆ Protective transparent cover for the element
- ◆ Compact panel mounting case

APPLICATION

High speed tripping functions requiring a number of simultaneous switching operations, interlocks in control and closing circuits

PRINCIPLE OF OPERATION

High speed tripping relays are voltage operated, attracted armature type with 8 contacts per relay. Each element is enclosed in a dust proof moulded, transparent, polycarbonate cover. Radio metal is used for the magnetic components such as the armature, the core and the yoke of the auxiliary relay to ensure good electrical performance.

The contacts are made of phosphor bronze and are nickel plated. The contact tips are made of pure silver. The use of these materials ensures very good contact performance.

TECHNICAL DATA

RATINGS

Rated voltage	:	110V, 220V, 250V DC & 230V AC
Operating range	:	75-120% of rated voltage
Reset range	:	75-120% of rated voltage
Operating time	:	Less than 10 ms at rated voltage
Reset time	:	Less than 20 ms at rated voltage
Operating indicator	:	Mechanical flag, electrical reset

BURDEN

Operated coil	:	8 Watts(maximum) at rated voltage
Reset coil	:	20 Watts(maximum) at rated voltage

ACCURACY

Operating value	:	+/- 5%
Operating time	:	+/- 5% or +/- 30ms
Instaneous time	:	Less than 40ms

CONTACT RATING

Make & Carry continuous	:	2500 VA with maximum of 5 A and 660V AC	:	2500 W with maximum of 5 A and 660V DC
Make & Carry for 3sec	:	7500 VA with maximum of 30 A and 660V AC	:	7500 W with maximum of 30 A and 660 V DC
Break	:	2500 VA with maximum of 5 A and 660 V AC	:	100W (Resistive), 50W(Inductive) with maximum of 5 A and 250 V DC
Operating temperature	:	-10 deg To +55 deg. Celsius		

CONTACTS DURABILITY

Unloaded contact	:	1,000,000 Operations
Loaded contact	:	1,00,000 Operations

MECHANICAL DESIGN

Weight	:	2Kg. (approx)
Case size	:	144sq mm, depth 125mm
Installation	:	Flush mounting
Panel cutout	:	138mm X 138mm

INSULATION

- 1) 2 KV RMS,50 Hz for 1 minute/2.5KV for 1sec between all terminals and case as per IEC 60255.
- 2) 1 KV RMS, 50 Hz for 1 minute across open contacts as per IEC 60255

STANDARD COMPLIANCE

Accuracy test	:	IEC 61810
Insulation test	:	IEC 60255

TERMINAL DIAGRAM

Note	:	Wiring diagram of tripping relays are given on request
------	---	--------------------------------------------------------

ORDERING INFORMATION

Relay type	:	JRV 192 T
Rated voltage	:	110V, 220V,250V DC & 230V AC